

GTL-152

Programmable industrial keyboard with
152 relegendable keys and optional
integrated magnetic card reader



(Ausführungsbeispiel)

Description

High-quality keyboard from the area of the POS keyboards. This keyboard is characterised by the following features:

- The keyboard is freely programmable. Each key can be occupied with up to 15 key codes.
That is why it is possible to release a series of key combinations just by pressing one key.
- Three different key caps are optionally available in different sizes: simple, double and fourfold. They can be individually labeled by the user. Different layouts thus become realizable.
- [Barcode](#) decoder integrated with support for TTL, WAND emulation and RS-232 interface.
Legible barcodes: UPC/EAN/JAN with add-2/5, code 39, code 128, ITF 2/5, codabar, code 11, code 93, MSI/plessey.
- A magnetic card reader can optionally be integrated with either one, two or three tracks.
- Durable Cherry MX-switch.

Specification**Mechanical data**

Dimensions:	450 or 450 or 450 or 450 x 220 or x 220 or x 220 or x 220 x 50 or x 50 or x 50 or x 50 mm
Weight:	2 kg or 2 kg or 2 kg or 2 kg
Housing:	Plastic
Color:	computer grey
Cable Length:	150 cm or 150 cm or 150 cm or 150 cm

Keys

Key Technology:	micro switch
Number of Keys:	152 or 152 or 152 or 152
Keyboard Layout:	free
Operational Life:	20 mio. keystrokes min. or 20 mio. keystrokes min. or 20 mio. keystrokes min. or 20 mio. keystrokes min.
Key Legend:	relegendable

Electric Data

Interface: AT
Operating Voltage: 5 or 5 or 5 or 5 ± 0,5 V or ± 0.5 V or ± 0,5 V or ± 0,5 V
Operating Current: 250 or 50 or 50 or 50 mA

Environment

Operating Temperature: from 0 °C or from 0 °C or from 0 °C or from 0 °C to 50 °C
or to 50 °C or to 50 °C or to 50 °C
Storage Temperature: from -20 °C or from -20 °C or from -20 °C or from -20 °C
to 70 °C or to 70 °C or to 70 °C or to 70 °C
Humidity: 10% to 85% relativ or 10% to 80% relativ

Order Information

Order No.	Article	
KP1156	GTL-152-PS/2	conectorPS2
KP1132	GTL-152D12-PS/2	interface PS/2
KP1133	GTL-152D23-PS/2	interface PS/2
KP1141	GTL-2+3152-PS/2	interface PS/2

sales@www.tastaturen.com Anrufen: (0 89) 89 43 99-0 Faxen: (0 89) 89 43 99-11