

KFT-105-V-Track-PS2-Ger

Membrane keyboard with integrated
trackball in a stainless steel housing.

**Description****Applications:**

This membrane keyboard with integrated [Trackball](#) in a stainless steel housing can be easily cleaned and disinfected and is therefore ideal for use in areas of food production, medicine, clean rooms and other industrial applications. The housing and the keyboard look great and can even be used in infoterminals.

Characteristics:

The keyboard in the housing is IP65 / NEMA4 dust and waterproof.

The German and US layouts are standard. Other layouts can be produced on demand.



Specification**Mechanical data**

Dimensions:	530,6 x 230 x 40 mm
Degree of Protection:	IP65
Housing:	High-Grade Steel
Cable Length:	180 cm

Keys

Key Technology:	short travel key
Number of Keys:	105 or 104
Keyboard Layout:	German
Operational Life:	3 mio. keystrokes min.
Actuation Force:	2,6 N
Stroke Travel:	0,4 mm
Key Legend:	silk screen

Electric Data

Additional Interface:	for Touchpad PS/2
-----------------------	-----------------------------------

Environment

Operating Temperature:	from 0 °C to +60 °C
Storage Temperature:	from -30 °C to +60 °C

Order No.	Article	
KF1255	KFT-105-V-Track-PS2-Ger	PS/2 interface, german layout
KF1254	KFT-105-V-Track-PS2-US	PS/2 interface, US layout

Accessories

Order No.	Article	
ZK1343	ZK-2-USB	

sales@www.tastaturen.com Anrufen: (0 89) 89 43 99-0 Faxen: (0 89) 89 43 99-11