

KVD-30-TT-PS2-Ger**Description****Applications:**

This keyboard has a wide range of uses in many fields due to its robust construction that is virtually indestructible. Such areas are points of information or ticketing machines.

Characteristics:

- The non removable and non inflammable key caps are made of high-grade steel. The front plate of 2.5 mm high-grade steel makes this keyboard particularly durable.
- This keyboard has 30 high-grade steel keys with a stroke of 3.5 mm. Therefore it is the first high-grade steel keyboard, that permits high-speed writing.

Interfaces:

- The keyboard has several connection types. The standard interface is [PS/2](#). The serial interface is available on demand.

The keyboard can be programmed and lasered to correspond to your needs. Just let us know what you need.

Specification

Mechanical data

Housing: Table-top housing
 Dimensions: 155 x 180 x 40,5 mm
 Degree of Protection: IP65
 Housing: Metal
 Cable Length: 180 cm

Keys

Key Technology: conductiv rubber
 Number of Keys: 30
 Keyboard Layout: numpad & German
 Operational Life: 10 mio. keystrokes min.
 Actuation Force: 0,65 N
 Stroke Travel: 3,25 ± 0,25 mm
 Key Legend: Laser

Electric Data

Interface: [PS/2](#)
 Operating Voltage: 5 V
 Operating Current: 50 mA

Environment

Operating Temperature: from -20 °C to +60 °C
 Storage Temperature: from -40 °C to +70 °C

Order Information

Order No.	Article	
KV1193	KVD-30-TT-PS2-Ger	PS/2 interface.german laout
KV1196	KVD-30-TT-PS2-US	PS/2 interface. US layout

sales@www.tastaturen.com Anrufen: (0 89) 89 43 99-0 Faxen: (0 89) 89 43 99-11