www.tastaturen.com®

KVD-86-TT Vandalresistent Highgrade Steel Keyboard Table Top Version

Vandal-resistent high-grade steel keyboard with integrated trackball.



Description

Applications:

This keyboard has a wide range of uses in many feilds due to its robust construction that is virtually indestructible. Such areas are points of information or ticketing mashines.

Characteristics of the keyboard:

- With their long travel keys with a stroke of 3.5 mm they are the first stainless steel keyboards, which enable confortable high-speed writing. This makes a more effective and more ergonomic operation possible.
- The laser-etched key caps do not allow the legends to wear off, they cannot be pulled out and are not inflammable.
- The thick front plates of 2.5 mm high-grade steel make these keyboards extremely durable and protects them from effects by force.

Dust- and waterproof according to DIN IP65 (front)

Characteristics of the Trackball:

- 38 mm Stainless Steel Trackball
- Very long lifespan due to its steel bearing shafts.



Specification

Mechanical data

Dimensions: 410 x 180 x 50 mm

Degree of Protection: IP65

Housing: High-Grade Steel

Cable Length: 180 cm

Keys

Key Technology: carbon contact

Number of Keys: 86

Keyboard Layout: German

Operational Life: 3 mio. keystrokes min.

Actuation Force: 0,25 N
Stroke Travel: 3,23 mm
Key Legend: Laser

Electric Data

Interface: PS/2

Additional Interface: for <u>Trackball</u> PS/2

Environment

Operating Temperature: from -20 $^{\circ}$ C to +60 $^{\circ}$ C Storage Temperature: from -40 $^{\circ}$ C to +70 $^{\circ}$ C

Additional Information

Diameter Trackball: 38 mm

Order No.	Article	
KV1113	KVD-86-TT-PS/2-Ger	PS/2 interface, german layout
KV1304	KVD-86-TT-PS/2-IT	PS/2 interface, italian layout
KV1165	KVD-86-TT-PS/2-US	PS/2 interface, US layout
KV1212	KVD-86-TT-USB-Ger	USB interface, german layout
KV1213	KVD-86-TT-USB-US	USB interface, US layout

Links

Click!	Titel
	KVD-Series Stainless Steel Keyboards Vandal proof Keyboards.

sales@tastaturen.com Telefon: (0 81 42) 66 95 8-0 Fax: (0 81 42) 66 95 8-11