

KVS-105- Front

Rugged keyboard made of stainless steel for front panel mounting.

**Description**

This keyboard has the layout of a standard keyboard. In order to save room, the NUM-block was left out.

If the NUM-block is needed, there is another version of this keyboard which you can find [HERE](#)

Like the other keyboards of the fullsize-range this keyboard is water- and dust proof to IP65 and has a good tactile feel due to the raised keycaps.

As front-panel mounted version with integrated staybolts this keyboard can be easily integrated into an existing housing.

For further information you can go to the [main page](#) of this keyboard range.

Specification**Mechanical data**

Housing:	High-Grade Steel
Degree of Protection:	IP65
Dimensions:	449 x 145,4 x 38 mm
Cable Length:	180 cm

Keys

Key Technology:	membrane
Number of Keys:	102
Keyboard Layout:	MF2-Country
Operational Life:	10 mio. keystrokes min.
Stroke Force:	1,5 ± 0,2 N
Stroke Travel:	1,68 mm
Key Legend:	Laser

Electric Data

Interface:	PS/2
------------	----------------------

Additional Interface: for [Trackball](#) PS/2

Environment

Operating Temperature: from -10 °C to +55 °C

Storage Temperature: from -25 °C to +70 °C

Order No.	Article	
KV1184	KVS-E105-F-PS/2-Ger	PS/2 interface, german layout
KV1185	KVS-E105-F-PS/2-US	PS/2 interface, US layout

sales@www.tastaturen.com Anrufen: (0 89) 89 43 99-0 Faxen: (0 89) 89 43 99-11