www.tastaturen.com[®]

KVS-105 Rear

Rugged keyboard made of stainless steel for back panel mounting.



Description

This keyboard has the layout of a standard keyboard. In order to save room, the NUM-block was left out.

If the NUM-block is needed, there is another version of this keyboard which you can find HERE

Like the other keybords of the fullsize-range this keyboard is water- and dust proof to IP65 and has a good tactile feel due to the raised keycaps.

As frontpanel mounted version with integrated staybolts this keyboard can be easily integrated into an existing housing.

For further information you can go to the main page of this keyboard range.

Specification

Mechanical data

Housing: Back-panel mounted Housing: High-Grade Steel

Degree of Protection: IP65

Dimensions: 464 x 162 x 29 mm

Cable Length: 180 cm

Keys

Key Technology: membrane

Number of Keys: 105

Operational Life: 10 mio. keystrokes min.

Stroke Force: $1,5 \pm 0,2 \text{ N}$ Stroke Travel: 1,6 mmKey Legend: Laser

Electric Data

Interface: PS/2

Page: KVS-105 Rear

Additional Interface: for <u>Trackball</u> PS/2

Environment

Operating Temperature: from -10 °C to +55 °C Storage Temperature: from -25 °C to +70 °C

Order No.	Article	
KV1220	KVS-E105-R-PS/2-Ger	PS/2 interface, german layout
KV1221	KVS-E105-R-PS/2-US	PS/2 interface, german layout

sales@www.tastaturen.com Anrufen: (0 89) 89 43 99-0 Faxen: (0 89) 89 43 99-11