

KVS-105 Rear

Rugged keyboard made of stainless steel for back panel mounting.

**Description**

This keyboard has the layout of a standard keyboard. In order to save room, the NUM-block was left out.

If the NUM-block is needed, there is another version of this keyboard which you can find [HERE](#)

Like the other keyboards of the fullsize-range this keyboard is water- and dust proof to [IP65](#) and has a good tactile feel due to the raised keycaps.

As frontpanel mounted version with integrated staybolts this keyboard can be easily integrated into an existing housing.

For further information you can go to the [main page](#) of this keyboard range.

Specification**Mechanical data**

Housing:	Back-panel mounted
Housing:	High-Grade Steel
Degree of Protection:	IP65
Dimensions:	464 x 162 x 29 mm
Cable Length:	180 cm

Keys

Key Technology:	membrane
Number of Keys:	105
Operational Life:	10 mio. keystrokes min.
Stroke Force:	1,5 ± 0,2 N
Stroke Travel:	1,6 mm
Key Legend:	Laser

Electric Data

Interface:	PS/2
------------	----------------------

Additional Interface: for [Trackball](#) PS/2

Environment

Operating Temperature: from -10 °C to +55 °C

Storage Temperature: from -25 °C to +70 °C

Order No.	Article	
KV1220	KVS-E105-R-PS/2-Ger	PS/2 interface, german layout
KV1221	KVS-E105-R-PS/2-US	PS/2 interface, german layout

sales@tastaturen.com **Telefon: (0 81 42) 66 95 8-0 Fax: (0 81 42) 66 95 8-11**