

### TVG-38 Stainless Steel Trackball in frontplate

A 38 mm stainless steel trackball and switches integrated into a steel front plate



### Description



- This [Trackball](#) has proven to be the ideal mouse input device in public areas.
- The characteristics of this trackball make it simple and exact to use, even for beginners.
- The integrated controller allows several adjustments to allow the exact integration into existing software environments.
- There are no special drivers needed.

**Customer specific changes can be made, such as a different size of the frontplate, other cable lengths, less or more keys (up to 4), etc.**

**Specification****Mechanical data**

Dimensions: 100 x 111 x 27 mm  
 Housing: Metal  
 Degree of Protection: [IP65](#) static  
 Cable Length: 180 cm

---

**Keys**

Key Technology: short travel key  
 Number of Keys: 2  
 Operational Life: > 1 mio. keystrokes

---

**Electric Data**

Additional Interface: for [Trackball PS/2](#)

---

**Temperature**

Operating Temperature: from 0 °C to +45 °C  
 Storage Temperature: from -10 °C to +60 °C




---

**Additional Information**

Ball Diameter: 38mm  
 Ball Speed: 203 pro rotation

Order No.	Article	
TV1014	TVG-38-2-Kurzhub-Edel/PS2	PS/2 interface
TV1015	TVG-38-2-Kurzhub-Edel/USB	USB interface
TV1019	TVG-38-2-Kurzhub-Edel/Seriell	serieller interface
TV1029	TVG-38-3-Kurzhub-Edel/PS2	PS/2 interface
TV1041	TVG-38-3-Kurzhub-Edel/Seriell	serieller interface
TV1037	TVG-38-3-Kurzhub-Edel/USB	USB Anschluss

**Links**

Click!	Titel
	<b>TVG-50 Stainless Steel Trackball in Frontplate</b> ø 50 mm Trackball integrated into a stainless steel front panel with two vandal resistant switches, IP65
	<b>TW-Series Trackball Modules</b> Optical or Mechanical Trackballs in different sizes
	<b>TVG-Series Stainless Steel Frontplates with integrated Mouse Modules</b> Vandalproof Series with Trackball or Touchpad and customized Frontplate.

[sales@tastaturen.com](mailto:sales@tastaturen.com) **Telefon: (089) 89 43 99-0 Fax: (089) 89 43 99-11**