

W60 Series

Waterproof programmable keyboard, available either as mountable or as table-top version with 60 single keys.

**Description****Applications:**

- The W60 can be used in areas such as points of sales, banking, as well as in ticketing and of course all industrial environments.

Characteristics:

- The long travel keys with a travel of 3.25mm and the good tactile feedback makes this keyboard very comfortable to use.
- The contacts and the electronic components are both water and dust proof.
- The software used to program the keyboard is simple to use and is included in the shipment.

You can find all further information on the [main page of the W30/W60/W90 series.](#)

Specification**Mechanical data**

Dimensions:	228,6 x 185 x 39,35 mm
	205 x 185, x 39,35 mm
Weight:	520 kg
Degree of Protection:	IP65
Housing:	Plastic
Degree of Protection:	IP65
Housing:	Plastic
Color:	computer grey
Cable Length:	200 cm

Keys

Number of Keys:	60
Keyboard Layout:	free
Operational Life:	10 mio. keystrokes
Actuation Force:	0,65,
Stroke Travel:	3,25 mm

Electric Data

Interface: AT
 Operating Voltage: +5 V
 Operating Current: 50 mA

Temperature

Operating Temperature: von -20 °C bis +60 °C
 Storage Temperature: von -40 °C bis +70 °C

Order No.	Article	
Table Top Housing		
KW1215	W60-PS/2-Tisch	PS/2 interface
KW1068	W60-AT-Tisch	AT interface
KW1085	W60-RS232-Tisch	serial interface
KW1216	W60-PS/2-Einbau	PS/2 interface
KW1088	W60-AT-Einbau	AT interface
KW1187	W60-RS232-Einbau	serial interface

Accessories

Order No.	Article	
ZT1042	KWD-1x1-Tastenkappe	keycaps 1x1
ZT1013	KWD-1x2-Tastenkappe	keycaps 1x2
ZT1014	KWD-2x2-Tastenkappe	keycaps 2x2
ZK1029	COM 9255 	adapter PS/2 to AT
ZS1211	Skin-W60	key skin for 60 keys
ZK1280	Einbaurahmen W60	frame for built in version
ZT1106	KWD-Beschriftungsbogen	self-adhesive foil for own legends
ZX1180	DSUB 25 -> 9 F/F	25-pin to 9-pin DSub adapter

Links

Click!	Titel
	W-Series with 30, 60 or 90 keys Waterproof and free programmable keyboard with 30, 60 or 90 relegendable keys. Table top version or build-in version.