

W90 Series

Waterproof programmable keyboard, available either as mountable or as table-top version with 90 single keys.

**Description****Applications:**

- The W90 can be used in areas such as points of sales, banking, as well as in ticketing and of course all industrial environments.

Characteristics:

- The long travel keys with a travel of 3.25mm and the good tactile feedback makes this keyboard very comfortable to use.
- The contacts and the electronic components are both water and dust proof.
- The software used to program the keyboard is simple to use and is included in the shipment.

You can find all further information on the [main page of the W30/W60/W90 series.](#)

Specification**Mechanical data**

Dimensions:	323,85 x 185 x 39,35 mm
	304 x 185 x 39,35mm
Weight:	0,520 kg,
Degree of Protection:	IP65
Housing:	Plastic
Degree of Protection:	IP65
Housing:	Plastic
Color:	computer grey
Cable Length:	200 cm,

Keys

Number of Keys:	90
Keyboard Layout:	free
Operational Life:	10 mio. keystrokes,
Actuation Force:	65 N
Stroke Travel:	3,25 mm

Electric Data

Interface:	RS232, AT
Operating Voltage:	+5 V
Operating Current:	50 mA

Temperature


Operating Temperature:	von -20 °C from +60 °C
Storage Temperature:	von -40°C from +70 °C

Order No.	Article	
Table Top Housing		
KW1218	W90-PS/2-Tisch	PS/2 interface
KW1069	W90-AT-Tisch	AT interface
KW1086	W90-RS232-Tisch	serial interface
Built-in Version		
KW1219	W90-PS/2-Einbau	PS/2 interface
KW2084	W90-AT-Einbau	AT interface
KW1089	W90-RS232-Einbau	serial interface

Accessories

Order No.	Article	
ZT1042	KWD-1x1-Tastenkappe	keycaps 1x1
ZT1013	KWD-1x2-Tastenkappe	keycaps 1x2
ZT1014	KWD-2x2-Tastenkappe	keycaps 2x2
ZT1106	KWD-Beschriftungsbogen	self-adhesive foil for own legends
ZX1180	DSub 25 -> 9 F/F	25-pin to 9-pin DSub adapter

Links

Click!	Titel
	W-Series with 30, 60 or 90 keys Waterproof and free programmable keyboard with 30, 60 or 90 relegendable keys. Table top version or build-in version.

sales@www.tastaturen.com Anrufen: (0 89) 89 43 99-0 Faxen: (0 89) 89 43 99-11